

Specifications

Model	M6040	M7040	M8540	M9540
Engine				
Type (Make: Kubota)	V3307-DI-TE3, E-CDIS, Direct Injection		V3800-DI-TE3, E-CDIS, Direct Injection	
No. of cylinders / Aspiration	4 / Turbocharged			
Rated speed rpm	2600			
Engine gross power HP	66.0	73.6	89.4	98.7
Engine net power HP	63.5	71.0	85.5	95.0
PTO power HP	56.0	64.0	76.0	84.0
Total displacement cm ³	3331		3769	
Fuel tank capacity ℓ	70 / 90		90 / 110	
Alternator amp	45 / 60			
Transmission				
No. of speeds	ROPS	15 forward / 15 reverse	-	
	Cab	15 forward / 15 reverse	36 forward / 36 reverse	
Max. speed km/h		38	39	
Main gear shift		5/Fully synchronised		6/Fully synchronised
Hydraulic shuttle		Standard, column-mounted lever		
Main clutch type		Hydraulic multi-plate wet disc		
Brake type		Hydraulic wet discs, 4 wheel braking		
Trailer brake		Option	Standard	
4WD engagement system		Electro-hydraulic		
Differential lock (Front / Rear)		Limited Slip Automatic Differential / Mechanical Differential Lock	Limited Slip Automatic Differential / Hydraulic Differential Lock	
PTO				
PTO type		Live-independent PTO, electro-hydraulic clutch		
Speed rpm		540/540E	540/1000	
Hydraulics				
Pump capacity (3-point hitch) ℓ/min.		61.0	64.3	
3-point hitch		Quick-hitch lower link ends, telescopic stabilisers		
Category		I / II	II	
Control system		Position, draft (top link sensing) & mix control		
Lift capacity at link end kg		2300	4100	
No. of standard remote valves		2 standard (3rd & flow control valve optional)		
Other features				
Steering		Hydrostatic power steering		
Bonnet type		Full open, slanted, steel		
Deck type / Pedal type		Semi-flat deck / Hanging pedals		
Panel type		Electronic		
Fender shape		Standard		
Standard tyre size (Front / Rear)		320/85R20 / 420/85R30		360/70R24 / 480/70R34
Dimensions & weight				
Overall length (ROPS / Cab) mm		3615 / 3675	- / 3675	- / 3955
Overall height (top of ROPS / Cab) mm		2495 / 2545	- / 2545	- / 2650
Overall width (min.) mm		1865		2005
Wheelbase mm		2050 / 2110		2250
Min. ground clearance mm		420 / 415	- / 415	- / 455
Tread width Front mm		1450,1537		1514,1608
Rear mm		1416-1733		1503-1695
Turning radius (w/o brake) m		3.4		3.8
Tractor weight (ROPS / Cab) kg		2450 / 2730	- / 2730	- / 3305

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional, and not standard equipment.

Please contact your local Kubota dealer for warranty, safety or product information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

©2008 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 214500 Fax (01844) 216685
E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>