

Specifications

Model	F2880		4WD		F3680
Engine					
Model		Kubota D1105		Kubota V1505	
Type		Liquid-cooled diesel (3 cyl)		Liquid-cooled diesel (4 cyl)	
Max. horsepower		HP	28	36	
Total displacement		cm ³	1,123	1,498	
Air cleaner		Type	Dual element		Standard
		Air restriction indicator	N/A		
Alternator				12 V, 40A	
Fuel tank capacity		ℓ	61.0		
Transmission					
Type		HST (F2/R2)			
Max. travel speed		Forward / Reverse	km/h (mph)		
4WD mode select		Auto-assist 4WD with dual acting overrunning clutch/locked 4WD			
Differential lock		Standard			
Cruise control		Optional			
Tyre					
Front		24×12-12			
Rear		18×9.5-8			
Brake		Wet discs			
Steering					
Type		Hydrostatic power			
Tilt steering		Standard			
Dimension					
Tread (F/R)		mm (in.)	1063 (41.8)/1045 (41.1)		
Wheel base		mm (in.)	1,300 (52.0)		
Overall length		mm (in.)	2,500 (100.0)		
Overall width		mm (in.)	1,370 (54.8)		
Overall height (w/o ROPS)		mm (in.)	1,350 (54.0)		
Weight (w/o ROPS)		kg (lbs.)	727 (1603)	744 (1640)	
Ground clearance		mm (in.)	185 (7.4)		
Mower mounting					
Type		Independent live, Shaft drive			
PTO revolution		2,545			
Clutch		Wet multi discs, hydraulic			
Lift system		Hydraulic 2-point hitch			
Tilt angle		Degrees	90		
Tilt assist		Standard			
Weight transfer		Standard			
Others					
Fuel gauge		Electric meter			
Tachometer		Optional			
Toolbox		Standard			
Seat		Reclining suspension seat			
Cup holder		Standard			
ROPS		Optional			

Mower Specifications

Model	RCK60-F36	RCK72-F36	RCK60R-F36	RCK72R-F36
Discharge	Side discharge		Rear discharge	
Cutting width	mm (in.)	1,520 (60)	1,826 (72)	1,520 (60)
Cutting height	mm (in.)	25 (1) - 127 (5)		
Cutting height adjustment	mm (in.)	Each 6.4 (0.25)		
Depth	mm (in.)	140 (5.5)		
Deck pan	Welded			
Thickness	mm (in.)	4.5 (0.18)		
Number of blades	3			
Turn assist brake	N/A	Standard	N/A	Standard
Mulch kit	Optional			

The company reserves the right to change the above specifications without notice.
 This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information.
 For your safety, KUBOTA strongly recommends the use of a Roll Over Protective Structure (ROPS) and seat belt in almost all applications.

©2007 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
 Phone Thame (01844) 214500 Fax (01844) 216685
 Web site: <http://www.kubota.co.uk/>
 E-mail: sales@kubota.co.uk