

F**F2680E/F3080/F3680****Kubota****SPECIFICATIONS****Specifications**

Model	F2680E		F3080	F3680
	2WD		4WD	
Engine				
Model	Kubota D1105		Kubota D1305	Kubota V1505
Type	Liquid-cooled diesel (3 cyl)			Liquid-cooled diesel (4 cyl)
Max. horsepower	HP	25.5	30	36
Total displacement	cu.in. (cm ³)	68.6 (1,123)	77.0 (1,261)	91.4 (1,498)
Air cleaner	Type	Dual element		Standard
	Air restriction indicator	N/A		
Alternator		12 V, 40A		
Fuel tank capacity	U.S. gals. (ℓ)	16.1 (61.0)		
Transmission				
Type		HST (F2/R2)		
Max. travel speed	Forward / Reverse	mph (km/h)		
4WD mode select		-	Auto-assist 4WD with dual acting overrunning clutch/locked 4WD	
Differential lock		Standard		
Cruise control		Optional		
Tire				
Front		23×10.5-12	24×12-12	
Rear		16×6.5-8	18×9.5-8	
Brake				
		Wet discs		
Steering				
Type		Hydrostatic power		
Tilt steering		Standard		
Turn assist brake		Optional		
Dimension				
Tread (F/R)	in. (mm)	38.4 (975)/34.4 (875)	41.8 (1063)/40.2 (1020)	
Wheel base	in. (mm)	51.2 (1,300)		
Overall length	in. (mm)	96.5 (2,450)		
Overall width	in. (mm)	48.8 (1,240)	53.9 (1,370)	
Overall height	in. (mm)	78.2 (1,985)		
Weight	lbs. (kg)	1,594 (723)	1,656 (751)	1,687 (765)
Ground clearance	in. (mm)	7.4 (188)		
Mower mounting				
Type		Independent live, Shaft drive		
PTO revolution		2,545		
Clutch		Wet multi discs, hydraulic		
Lift system		Hydraulic 2-point hitch		
Tilt angle	Degrees	90		
Tilt assist		Standard		
Weight transfer		Standard		
Others				
Fuel gauge		Electric meter		
Tachometer		Optional		
Toolbox		Standard		
Seat		Reclining suspension seat		
Cup holder		Standard		

Mower Specifications

Model	RCK60P-F36	RCK72P-F36	RCK60R-F36	RCK72R-F36
Discharge	Side discharge		Rear discharge	
Cutting width	in. (mm)	60 (1,520)	72 (1,826)	60 (1,520)
Cutting height	in. (mm)	1 (25)-5 (127)		
Cutting height adjustment	in. (mm)	Each 0.25 (6.4)		
Depth	in. (mm)	5.5 (140)		
Deck pan		Welded		
Thickness	in. (mm)	0.18 (4.5)		
Number of blades		3		
Front baffle kit		Optional		N/A
Mulch kit		Optional		

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information.

For your safety, KUBOTA strongly recommends the use of a Roll Over Protective Structure (ROPS) and seat belt in almost all applications.